



High capacity tank with collapsible structure

The tank is suitable, for example, for helicopter firefighting using the bambi sac or for repumping materials at places difficult to reach.



- ▶ Rapid assembly
- ▶ Low weight
- ▶ Simple and robust structure is made of a light alloy and stainless steel
- ▶ Packed construction takes minimal space
- ▶ Volume of 5 000–35 000 litres



**Utility water reservoir
or a collection tank
for hazardous substances**



The whole tank can be erected by a single person in several minutes

Ball valve C52 and ETX 04

Process of tank draining so as there remains no water

Accessory: fill elbow

No tools are needed to assemble the tank; its parts are connected using special pegs

Collapsible load-bearing leg for inclined ground

Technical details

The bund is made of a highly resistant PES/PVC material providing the temperature range of use of -30 °C to +70 °C. The material is resistant against chemical and oil substances (see Chemical resistance certificate in the relevant chapter at the end of catalogue), thereby providing enhanced potential of use in environmental accidents. The tank can be filled very quickly using the filling elbow with C52 (B75) end piece in the upper part of the structure. A fill / discharge valve is located in the bottom part of the tank. If the tank is not placed on an even surface, installing a protective pad under the bottom of the tank is recommended.

Fastening lugs are used to tighten and unfold the bottom of the tank; the structure can be anchored through openings in the footing part

| Volume (l) | 5000 | 7500 | 20 000 | 35 000 |
|--|------------------------|------------------------|------------------------|------------------------|
| Diameter (mm) | 2300 | 2700 | 4200 | 5500 |
| Height (mm) | 1300 | 1300 | 1500 | 1500 |
| Vertical supports/load-bearing legs | 6/2 | 6/2 | 10/4 | 12/4 |
| Package dimensions (mm) and weight of the structure (kg) | 300 × 200 × 1350 30 | 300 × 200 × 1600 30 | 500 × 300 × 1550 50 | 500 × 300 × 1550 60 |
| Package dimensions (mm) and weight of the foil (kg) | 300 × 200 × 800 20 | 300 × 200 × 800 25 | 400 × 400 × 1000 50 | 600 × 400 × 1100 70 |
| Accessories | | | | |
| Protective pad (mm) | 2500 × 2500 | 3000 × 3000 | 4500 × 4500 | 6000 × 6000 |
| Fill elbow C52/B75 | yes | yes | yes | yes |
| Ball valve C52/B75 | yes | yes | yes | yes |
| Reduction coupling C52/B75 | yes | yes | yes | yes |
| Ball valve ETX 04 | yes | yes | yes | yes |