## Colleracibl

High capacity tank

Usage

## Collapsible containment tank

Fire brigade

Water & Forest

> The self-supporting containment tank is designed to be used as a utility water reservoir or a collection tank for hazardous substances. The tank is suitable for pumping liquids from accidental spillages or as a backup water reservoir at difficult to reach areas.



ICCOTAR HazMat

- Rapid assembly
- Light weight
- Variants Octagon and Hexagon
- Side handles for easy manipulation

PATENTED

- Perimeter belt for better strengthening of sides
- Possibility of adding of drain hole and ball valve
- Volumes of 264–793 gallons



Backup water reservoir at difficult to reach areas





## **Technical details**

The tanks are made of highly resistant PES/PVC coated material with textile reinforcement. The material is resistant against chemical and oil substances (see Chemical resistance certificate in the relevant chapter at the end of catalog), thereby providing enhanced potential of use in environmental accidents. The sidewalls have 0.24 in thick polypropylene reinforcements welded inside. The temperature range of use is from -22 °F to +158 °F.

It is necessary for the tank to be placed on an even surface, without any sharp object. It is recommended to place the tank on a protective pad to increase its lifetime.

The product is protected by registered utility model (technical patent) no. 22118 lodged with the Industrial Property Office.

Туре	ET HX 1000	ET HX 2000	ET OCT 3000
Volume (gal)	264	528	793
Diameter inscribed/described (in)	51/59	54/63	91/104
Height (in)	28	32	26
The width of one side (in)	30	39	38
Weight (lb)	66	110	121
Standard accesories			
Bag	yes	yes	yes
Peripheral belts	yes	yes	yes
Protective pad	yes	yes	yes
Optional accessories at extra cost			
Drain hole C52/B75/other	yes	yes	yes
Ball valve C52/B75/other	yes	yes	yes